

**DULUX TRADE ANTI  
GRAFFITI CLEARCOAT****816****PRODUCT INFORMATION**

<b>Typical Use</b>	<p><b>Dulux Trade</b> Anti Graffiti Clearcoat is a two pack, water based coating for use over existing sound coatings or clean, dry and laitance free uncoated masonry surfaces. <b>Dulux Trade</b> Anti Graffiti Clearcoat dries to a tough gloss finish that has good impact &amp; abrasive properties, protecting areas that are prone to graffiti. <b>Dulux Trade</b> Anti Graffiti Clearcoat can be used in areas where low odour coatings are required, e.g. hospitals, schools &amp; public buildings.</p> <p>Before preparing any surface for painting, read the Safety, Health &amp; Environmental information on page 2 about old lead-based paints.</p>
<b>Pack Size</b>	3.91 litre Base and 1.09 litre Activator.
<b>Colour Range</b>	N/A
<b>Composition (nominal)</b>	<b>Pigment:</b> N/A <b>Binder:</b> Polyacrylic / Isocyanate <b>Solvent:</b> Water.
<b>Volume Solids</b>	40% (Nominal)
<b>Mixing Ratio</b>	<p>Supplied in correct proportions. Add all of the Activator to the Base container and mix thoroughly for at least 5 minutes, until the product is smooth and even.</p> <p>Do not mix part units. Badly activated or incorrectly mixed materials will affect performance and may cause early failure or discolouration.</p>
<b>Thinning</b>	Ready for use when mixed. If required, add a maximum of 10% clean water to activated paint.
<b>Application Method</b>	Application is by brush or roller only. <b>For health and safety reasons this product must not under any circumstances be applied by spray.</b>
<b>Pot Life</b>	1-2 Hours (Depending on prevailing conditions).
<b>Film Thickness</b>	<p><i>Film thickness will be dependent on the coverage achieved.</i></p> <p><b>Wet:</b> 75 microns. <b>Dry:</b> 30 microns.</p>
<b>Drying Times</b>	<p><i>Single coat at standard thickness:</i></p> <p><b>Touch Dry:</b> At 20°C - 6 hours. <b>Recoat:</b> Minimum 16 hours and maximum - 7 days. Hard dry after 16 hours.</p>
<b>Theoretical Coverage</b>	8m <sup>2</sup> per litre.
<b>Cleaning Up</b>	After use, remove as much paint as possible from equipment before cleaning with clean water. Do not use or store in extremes of temperature and protect from frost.

**SURFACE PREPARATION**

To get the best results with **Dulux Trade** Anti Graffiti Clearcoat, make sure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry), and free from any contaminants such as loose particles, dust, grease etc. It is recommended that a small test area is applied before treating the entire surface to ensure compatibility.

**SYSTEM INFORMATION**

Stir thoroughly before use.

Apply 1 or 2 coats of **Dulux Trade** Anti Graffiti Clearcoat to sound, clean surfaces. Avoid over application.

**Note:** Do not apply over underbound coatings e.g. distemper or non cross-linked flexible coatings e.g. Acrylated Rubber, Chlorinated Rubber.

## SAFETY, HEALTH & ENVIRONMENTAL INFORMATION

### DULUX TRADE ANTI GRAFFITI CLEARCOAT BASE

#### WATER-BASED CLEARCOAT

**RESTRICTED TO PROFESSIONAL USERS, WHO ARE SUITABLY TRAINED.**

**Flammable.**

**Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.**

Keep away from sources of ignition - no smoking.

Avoid release to the environment. Refer to special instructions/Safety data sheet. This includes waste hazard categories.

EU limit value for this product (cat A/j) : 140g/l (2007) / 140g/l (2010)

This product contains max. 75g/l VOC

### DULUX TRADE ANTI GRAFFITI CLEARCOAT ACTIVATOR

#### ISOCYANATE-BASED ACTIVATOR

**RESTRICTED TO PROFESSIONAL USERS WHO ARE SUITABLY TRAINED.**

**May cause sensitisation by inhalation and skin contact.**

**Contains aliphatic polyisocyanate and hexamethylene-di-isocyanate.**

Before use refer to safety data sheet. This includes waste hazard categories.

Contains isocyanates. See information supplied by the manufacturer.

EU limit value for this product (cat A/j) : 140g/l (2007) / 140g/l (2010)

This product contains max. 75g/l VOC



**HARMFUL**

### DULUX TRADE ANTI-GRAFFITI ANTI GRAFFITI CLEARCOAT BASE & ACTIVATOR

Do not apply by spray.

Use only in well ventilated areas.

Do not breathe vapour.

Avoid contact with skin and eyes.

Wear suitable protective clothing and gloves.

When applying it is advisable to wear eye protection.

Wear a dust mask if applying by roller.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent, thinners or white spirit.

Keep out of the reach of children.

Keep away from food, drink and animal feeding stuffs.

If swallowed, seek medical advice immediately and show this container or label.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

In case of accident by inhalation: remove casualty to fresh air and keep at rest.

Do not use or store by hanging on a hook.

Do not empty into drains or watercourses.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact::

ICI Paints Technical Group, at:

ICI Paints, Wexham Road, Slough

SL2 5DS.

Tel: 0870 242 1100 (national call rates apply)

See [www.duluxtrade.co.uk](http://www.duluxtrade.co.uk)

VOC Content Low 0.30% - 7.99%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux Trade and the ICI Roundel are trademarks of ICI

© ICI 06 (020506IT)

